







ISO 9001 國際品質認證
ISO 9001 CERTIFICATE

松 暉 電 機 工 業 股 份 有 限 公 司
SONG HUEI ELECTRIC CO., LTD.
佛 山 市 松 暉 電 機 科 技 有 限 公 司
FOSHAN SONG HUEI ELECTRIC CO., LTD.


耐候性 Weather Performance		
項目 Item	測試條件 Test Conditions	規格 Performance
耐濕度 Humidity test	置於溫度 $40 \pm 2\text{ }^{\circ}\text{C}$ ，溼度 $90 \sim 95\text{ \% RH}$ ，500 小時後，放於正常環境下 1 小時，然後 1 小時內測試。 Testing switch being kept in the conditions at $40 \pm 2\text{ }^{\circ}\text{C}$ and $90 \sim 95\text{ \% RH}$ for 500 hours in a normal ambient condition for 1 hour. then to be measured within 1 hour.	絕緣電阻在 $10\text{ M}\Omega$ 以上，DC 500 V，耐壓 AC 600 V 持續1分鐘，操作力矩變化在 $\pm 30\text{ \%}$ 之內，各部位無損壞，無機械性能異常。電阻變化 $\pm 10\text{ \%}$ 以內。 Insulation resistance is more than $10\text{ M}\Omega$ under DC 500 V, and also withstand voltage AC 600 V for 1 minute. The operating torque shall be within $\pm 30\text{ \%}$ of initial value, and every parts should not defected in appearance and mechanical performance. The resistance change shall be within $\pm 10\text{ \%}$.
耐熱性 Heat test	置於溫度 $125 \pm 2\text{ }^{\circ}\text{C}$ ，500 小時後，放於正常環境下 1 小時，然後 1 小時內測試。 Testing switch being kept in the conditions at $125 \pm 2\text{ }^{\circ}\text{C}$ for 500 hours and then in a normal ambient condition for 1 hour. Then to be measured within 1 hour.	
低溫特性 Cold test	置於溫度 $-55 \pm 2\text{ }^{\circ}\text{C}$ ，500 小時後，放於正常環境下 1 小時，然後 1 小時內測試。 Testing switch being kept in the conditions at $-55 \pm 2\text{ }^{\circ}\text{C}$ for 500 hours and then in a normal ambient condition for 1 hour. then to be measured within 1 hour.	
耐久性 Durability		
項目 Item	測試條件 Test Conditions	規格 Performance
壽命 (無負荷) Life test (Without load)	無負荷狀態連續測試，速度為 $6 \sim 10$ 回 / 分，總次數 200 次。 200 cycles of operation shall be performed continuously at the rate of $6 \sim 10$ cycles / minute without load.	絕緣電阻在 $10\text{ M}\Omega$ 以上，DC 500 V，耐壓 AC 600 V 持續 1 分鐘，操作力矩變化在 $\pm 30\text{ \%}$ 之內，各部位無損壞，無機械性能異常。 Insulation resistance is more than $10\text{ M}\Omega$ under DC 500 V, and also withstand voltage AC 600 V for 1 minute. The operating torque shall be within $\pm 30\text{ \%}$ of initial value, and every parts should not defected in appearance and mechanical performance.



Mounting Hole



CIRCUIT



Non notation tolerance	
< 10	±0.3
10 ~ 100	±0.5
> 100	±0.8



SONG HUEI ELECTRIC CO., LTD.
FOSHAN SONG HUEI ELECTRIC CO., LTD.

MODEL: 3362W/0286

Approval



Checked



Projected



UNIT	mm	SCALE	3:1
VERSION	1.1	DATE	2012.08.10
DRAWING NO.	3362-004		

④

③

②

①

整理图元

ISSUE

SUBJECT

何鴻根

NAME

2018. 12. 18

DATE

RECORD